



Material 材質	Hardness 硬度
SK-3	HRC56 ~60
FDAC	HRC33 ~38

Type	L	D							
		6	8	10	12	13	14	16	20
JH090	20	5.8	6.2	7.4	9.2				
	25	5.8	6.2	7.6	9.2				
	30	5.8	6.2	7.8	9.2	16.0	16.0	18.0	33.0
	35	5.8	6.6	7.8	9.2	16.0	16.0	18.0	33.0
	40	5.8	6.6	7.8	10.0	16.0	16.0	18.0	34.0
	45	6.2	7.0	8.0	10.4	16.0	16.0	19.0	34.0
	50	6.2	7.0	8.4	11.0	16.4	16.4	19.0	35.0
	55	6.6	7.8	9.4	11.6	19.0	19.0	21.6	35.0
	60	6.6	7.8	9.4	11.6	19.0	19.0	21.6	37.0
	65	7.8	8.6	10.2	12.4	21.0	21.0	23.0	38.0
	70	7.8	8.6	10.4	12.8	21.0	21.0	23.0	38.0
	75	9.0	9.8	11.0	13.2	24.0	24.0	26.0	40.0
	80	9.8	10.0	11.4	13.2	24.0	24.0	26.0	40.0
	90	11.4	12.0	12.6	15.2	25.0	25.0	28.0	43.0
	100	13.4	14.0	15.0	17.2	29.0	29.0	30.0	51.0
	110	15.4	16.4	17.0	19.2	33.0	33.0	34.0	51.0
	120	17.4	18.4	19.0	22.0	37.0	37.0	36.0	61.0
			21.4	21.4	23.0	42.0	42.0	43.0	67.0
			25.4	23.4	28.0	46.0	46.0	46.0	69.0
			29.4	15.4	32.0	54.0	54.0	54.0	85.0

● Order: Type x

攻牙Thread: 6ΦM4x0.7 8ΦM5x0.8 10ΦM6x1.0 12ΦM8x1.25 14MΦ8x1.25 16MΦ8x1.25 20MΦ8x1.25

E: L30内 e=10< L30~50 e15< L50以上e20

2D下载

3D下载

返回索引